

LOADS

Bolt anchor FBN II GS

Highest permissible loads for a single anchor¹⁾ in concrete C20/25⁴⁾

For the design the complete approval ETA - 07/02 1 1 has to be considered.

					Non-cracked concrete			
Type	Min. effective anchorage depth $h_{ef,min}$ [mm]	Max. effective anchorage depth $h_{ef,max}$ [mm]	Min. member thickness h_{min} [mm]	Installation torque T_{inst} [Nm]	Permissible tensile load $N_{perm}^{3)}$ [kN]	Permissible shear load $V_{perm}^{3)}$ [kN]	Min. spacing $s_{min}^{2)}$ [mm]	Min. edge distance $c_{min}^{2)}$ [mm]
FBN II 12 GS	50		100	50,0	8,5	17,9	70	100
		65	120	50,0	12,6	17,9	70	70
FBN II 16 GS	65		120	100,0	12,6	29,0	90	120
		80	160	100,0	17,2	31,5	90	90

¹⁾ The partial safety factors for material resistance as regulated in the approval as well as a partial safety factor for load actions of $\gamma_L = 1,4$ are considered. As an single anchor counts e.g. an anchor with a spacing $s \geq 3 \times h_{ef}$ and an edge distance $c \geq 1,5 \times h_{ef}$. Accurate data see approval.

²⁾ Minimum possible axial spacings resp. edge distance while reducing the permissible load.

³⁾ For combinations of tensile loads, shear loads, bending moments as well as reduced edge

distances or spacings (anchor groups) see approval.

⁴⁾ For higher concrete strength classes up to C50/60 higher permissible loads may be possible.

⁵⁾ The anchorage depths smaller than 40 mm are only allowed for multiple use for non-structural applications.